



Nennvolumenstrom (ISO1217):	330 m ³ /h
Nominal flow rate (ISO1217):	330 m ³ /h
Betriebsdruck P ₀ min/max:	4...14 bar(g)
Working pressure P ₀ min/max:	4...14 bar(g)
Eintrittstemperatur T ₀ max:	70 °C
Inlet temperature T ₀ max:	70 °C
Umgebungstemperatur:	1...50 °C
Ambient Temperature:	1...50 °C
Kältemittel:	R404A/0.70 kg
Refrigerant:	R404A/0.70 kg
Kältem. Auslegungsdruk HD/HD:	32/23 bar
Refig. Design Pres. HD/LP:	32/23 bar
Elektrischer Anschluss:	1/230-240/50 pA/Hz
Power supply:	1/230-240/50 pA/Hz
Elektrische Leistung:	820/4.0 kW
Electric control power:	820/4.0 kW
Abfederung max:	10 l
Fuse protection max:	10 l



Beko RA 55 dryer

Reference # 4926
Year 2010
Available Immediately

Complete with

- 1x Beko / Drypoint persluchtdroger model RA55
- nominale capaciteit 330m³/uur

PRESTOTYPE BV
SCHELLINGWEG 9
1507 DR ZAANDAM
HOLLAND

TEL: +31 75 6313222
FAX: +31 75 6179965
SALES@PRESTOTYPE.COM
WWW.PRESTOTYPE.COM