



Nennvolumenstrom (ISO1217):	330 m <sup>3</sup> /h
Nominal flow rate (ISO1217):	330 m <sup>3</sup> /h
Betriebsdruck P <sub>0</sub> min/max:	4...14 bar(g)
Working pressure P <sub>0</sub> min/max:	4...14 bar(g)
Eintrittstemperatur T <sub>0</sub> max:	70 °C
Inlet temperature T <sub>0</sub> max:	70 °C
Umgebungstemperatur:	1...50 °C
Ambient Temperature:	1...50 °C
Kältemittel:	R404A/0.70 kg
Refrigerant:	R404A/0.70 kg
Kältem. Auslegungsdruk HD/HD:	32/23 bar
Refig. Design Pres. HD/LP:	32/23 bar
Elektrischer Anschluss:	1/230-240/50 pA/Hz
Power supply:	1/230-240/50 pA/Hz
Elektrische Leistung:	820/4.0 kW
Electric control power:	820/4.0 kW
Abfederung max:	10 l
Fuse protection max:	10 l



## Beko RA 55 dryer

**Reference #** 4926  
**Year** 2010  
**Available** Immediately

Complete with

- 1x Beko / Drypoint persluchtdroger model RA55
- nominale capaciteit 330m<sup>3</sup>/uur

PRESTOTYPE BV  
SCHELLINGWEG 9  
1507 DR ZAANDAM  
HOLLAND

TEL: +31 75 6313222  
FAX: +31 75 6179965  
[SALES@PRESTOTYPE.COM](mailto:SALES@PRESTOTYPE.COM)  
[WWW.PRESTOTYPE.COM](http://WWW.PRESTOTYPE.COM)